



## Xbrite: low maintenance, great appearance

Choose Xbrite® – as well as bringing you all the benefits of the Xlite® range, Xbrite wheels also come with a superior finish that takes less time and effort to keep your fleet looking extra special.

Based on the Xlite range of spin-forged aluminium wheels, Xbrite wheels are manufactured to world-class standards to meet your commercial vehicle needs. Stronger by design and 40% lighter than the standard steel equivalent, Xbrite offers real cost savings and improved performance for commercial vehicles.

Xbrite is tailored to your requirements, available in a range of sizes including 17.5", 19.5" and 22.5". Specially treated, the Xbrite range delivers the highest levels of corrosion resistance and shine to ensure your wheels not only perform to the highest possible standards, but also look fantastic.

## Xbrite: meeting your needs

- Look good: Xbrite ensures your fleet's wheels look great and are easy-to-clean with minimal requirements for chemical washing or high maintenance scheduling. Simply use mild soap.
- **40% lighter:** Our Xbrite wheels have an average weight of 24kg, allowing your vehicle to carry extra payloads, as well as providing significant fuel savings and reduced environmental impact.
- **5x stronger:** Xbrite is spin-forged from a single high-strength aluminium billet using state-of-the-art Computer Numeric Control (CNC) machines to create outstanding production accuracy. It is then specially heat treated to produce a maximum strength wheel.
  - For you, this means less wear and tear and the longest possible life for your wheels, tyres and axles, as well as greater ride comfort.
- Protected ALV valve: Our ALV valves are fitted on every wheel, precisely positioned to ensure that they are not damaged by stones thrown by the brake rotor.
- Meeting safety standards: All our wheels are rigorously tested to meet European Tyre and Rim Technical Organisation standards, ensuring both your fleet and the roads are safe.
- Guaranteed quality: Certified to TUV standards, Xbrite wheels have been independently audited for quality, ensuring you get the best product possible. We are so confident of the quality we offer that our Xbrite range comes with a five-year warranty.
- Supply chain traceability: We offer full traceability of all our wheels from manufacture to distribution, so you have complete peace of mind that Xbrite wheels are fully compliant.

## Range specifications:



|                    | Xbrite Part No. | Wheel Size (W x D) |    |    | Centre Bore (mm) | Pitch Circle Diameter (PCD) (mm) |             | HDS (offset) (mm) |              |      | Dual Mount |     |                 |
|--------------------|-----------------|--------------------|----|----|------------------|----------------------------------|-------------|-------------------|--------------|------|------------|-----|-----------------|
| 235,245 75 17.5    | CVAA274XB+      | 6.75 X 17.5        | 10 | 26 | 176              | 225                              | 121         | 141               | 14.4         | 3000 | YES        | YES | 70MS 07         |
| 245,265 70 19.5    | CVAA300XB+      | 7.50 X 19.5        | 8  | 26 | 221              | 275                              | 13 <b>3</b> | 155               | 19.2         | 3040 | YES        | YES | <b>TM-</b> 1670 |
| 245,265 70 19.5    | CVAA302XB+      | 7.50 X 19.5        | 8  | 32 | 221              | 275                              | 13 <b>3</b> | 155               | 19.2         | 3040 | YES        | YES | <b>TM-</b> 1670 |
| 255,275 70,80 22.5 | CVAA203XB+      | 7.50 X 22.5        | 10 | 26 | 281              | 335                              | 140         | 162               | 23.5         | 3550 | YES        | YES | 70MS 07         |
| 255,275 70,80 22.5 | CVAA288XB+      | 7.50 X 22.5        | 10 | 32 | 281              | 335                              | 140         | 162               | 23.3         | 3550 | YES        | YES | 70MS 07         |
| 295 60,80 22.5     | CVAA121XB+      | 8.25 X 22.5        | 10 | 26 | 281              | 335                              | 144         | 167               | 24.6         | 3650 | YES        | YES | TM-1670         |
| 295 60,80 22.5     | CVAA122XB+      | 8.25 X 22.5        | 10 | 32 | 281              | 335                              | 144         | 167               | 24.5         | 3650 | YES        | YES | TM-1670         |
| 315 60,70,80 22.5  | CVAA390XB+      | 9.00 X 22.5        | 10 | 26 | 281              | 335                              | 152         | 175               | 25. <b>9</b> | 4125 | YES        | YES | TR 545-27       |
| 315 60,70,80 22.5  | CVAA391XB+      | 9.00 X 22.5        | 10 | 32 | 281              | 335                              | 152         | 175               | 25.7         | 4125 | YES        | YES | TR 545-27       |
| 385 55,65 22.5     | CVAA003XB+5     | 11.75 X 22.5       | 10 | 26 | 281              | 335                              | 0           | 0                 | 24.4         | 5000 | NO         | NO  | TR542           |
| 385 55,65 22.5     | CVAA019XB+5     | 11.75 X 22.5       | 10 | 32 | 281              | 335                              | 0           | 0                 | 24.4         | 5000 | NO         | NO  | TR542           |
| 385 55,65 22.5     | CVAA392XB+      | 11.75 X 22.5       | 10 | 26 | 281              | 335                              | 120         | 0                 | 27.5         | 5000 | NO         | YES | TR542           |
| 385 55,65 22.5     | CVAA411XB+      | 11.75 X 22.5       | 10 | 32 | 281              | 335                              | 120         | 0                 | 27.3         | 5000 | NO         | YES | TR542           |
| 385 55,65 22.5     | CVAA059XB+      | 11.75 X 22.5       | 10 | 26 | 281              | 335                              | 135         | 0                 | 27.8         | 4500 | NO         | YES | TR542           |
| 385 55,65 22.5     | CVAA060XB+      | 11.75 X 22.5       | 10 | 32 | 281              | 335                              | 135         | 0                 | 27.8         | 4500 | NO         | YES | TR542           |
|                    |                 |                    |    |    |                  |                                  |             |                   |              |      |            |     |                 |



## Z Orite R

Spin-Forged Aluminium Wheels