



FORGED ALUMINIUM WHEELS



Size	Xlite Code			Stud Hole Diam. (mm)	Weight (kg)	Max Load (kg)	Inset (mm)	Offset. (mm)	Disk Thick. (mm)	N. Stud Holes	PCD (mm)	Central Bore (mm)	Dual Moun.	Air Valve
	BRUSH.	POLISH	X-BRITE											
6.75x17.5	274M	274P2	274XB	26	14,4	3.000	121	141	20,00	10	225	176,0	yes	70MS 07
7.50x19.5	300M	300P2	300XP	26	19,2	3.040	133	155	22,00	8	275	221,1	yes	TM1670
	302M	302P2	302XP	32	19,2									
7.50x22.5	203M	203P2	203XP	26	23,5	3.550	140	162	22,00	10	335	281,2	yes	70MS07
	288M	288P2	288XP	32	23,5									
8.25x22.5	121M	121P2	121XB	26	24,6	3.650	144	167	23,00	10	335	281,2	yes	TM1670
	122M	122P2	122XB	32	24,5									
9.00x22.5	435M	435P2	435XB	26	25,9	4.125	152	175	23,00	10	335	281,2	yes	TR545-27
	436M	436P2	436XB	32	25,7									
11.75x22.5	003M	003PO	003XB	26	24,4	5.000	0	-	24,00	10	335	281,2	no	TR542
	019M	019PO	019XB	32	24,2									
11.75x22.5	392M	392PO	392XB	26	27,5	5.000	120	-	27,50	10	335	281,2	no	TR542
	411M	411PO	411XB	32	27,3									
Only for Scania, Daf and Iveco for the Steering and tag axle														
11.75x22.5	059M	059PO	059XB	26	27,6	4.500	135	-	27,50	10	335	281,2	no	TR542
	060M	060PO	060XB	32	27,6									

- Legenda: M: Brushed - PO: Polished Outside - P2: Polished Inside and Outside - XB: Xbrite